Flux



Add visual interest to your garden with the Flux outdoor path light. A 360° light spread and cast aluminum construction with a powder-coated finish fits best along pathways, garden beds, and walkways.



| Model | Size | Watts | Delivered lumens | CRI | Color °T | Voltage |
|---|------|-------|---|-----|--|---------|
| LPP20-CC | 20" | 8 W | 360 lm | 80 | 2200, 2700, 3000, 3500, 4000 K | 12 VAC |
| Specifications | | | Finish | | Accessories | |
| Over 50,000 hours of service life 12VAC input | | | BK Black | | LCBL-50-16 50 feet of 16 gauge low-voltage wiring | |
| Ground stake included 93° beam angle | | | Power supplies | | LCBL-100-16 100 feet of 16 gauge low-voltage wiring | |
| Frosted lens Can be mounted to wood or concrete | | | LTRP-60-BK 60W, 120VAC 60Hz input 12VAC output low-voltage transformer | | LCBL-50-14 50 feet of 14 gauge low-voltage wiring | |
| (screws not included) Cast aluminum construction Switch-selectable CCT: 2200 K/2700 K/ 3000 K/3500 K/4000 K Suitable for wet locations 5-year warranty | | | LTR-300-BK 300W, 120VAC 60Hz input 12/13/14/15VAC output low-voltage transformer | | LCBL-100-14 100 feet of 14 gauge low-voltage wiring LCBL-100-12 100 feet of 12 gauge low-voltage wiring | |
| | | | | | | |
| | | | | | Note | |


LPP20-CC

Sold separately.

for more information.

Low-voltage transformer required.

Other color °T and finishes available, but may require MOQ's and longer lead times. Please contact your DALS representative



8-1/4"



